

---

<b>Print method</b>	7-pin shuttle impact dot matrix
---------------------	---------------------------------

<b>Technology</b>	Serial Impact Dot Matrix
-------------------	--------------------------

---

## Fonts & Styles

<b>Print Speed</b>	1.90 ~ 2.30 lps
--------------------	-----------------

<b>Column capacity slip</b>	35 cps / 42 cps
-----------------------------	-----------------

<b>Character size</b>	1.6 mm (W) x 2.9 mm (H) / 1.3 mm (W) x 2.9 mm (H)
-----------------------	---

<b>Character set</b>	95 Alphanumeric, 32 International, 128 x 4 Graphic
----------------------	--

<b>Characters per inch</b>	13.5 cpi / 16.2 cpi
----------------------------	---------------------

<b>Colour Printing</b>	Single Colour
------------------------	---------------

---

## Paper

<b>Paper Types</b>	Slip
--------------------	------

<b>Copy capability slip</b>	two copies plus one original
-----------------------------	------------------------------

<b>Paper size slip</b>	80 - 182 mm (W) x 69 - 257 mm (H)
------------------------	-----------------------------------

---

## Interfaces

<b>Interfaces</b>	RS-232, Drawer kick-out
-------------------	-------------------------

---

## Data Buffer

<b>Data Buffer</b>	512 Bytes or 35 Bytes
--------------------	-----------------------

---

## Power

<b>Power Supply</b>	PS-180 (option)
---------------------	-----------------

---

## General

<b>Product dimensions</b>	180 x 191 x 102 mm (Width x Depth x Height)
---------------------------	---

<b>Product weight</b>	1.6 kg
-----------------------	--------

<b>Colour</b>	Epson Cool White
---------------	------------------

<b>Installation</b>	horizontally
---------------------	--------------

<b>Interface connectors</b>	D.K.D. function (2 drivers)
-----------------------------	-----------------------------

<b>Noise Level</b>	Operation: 65 dB (A)
--------------------	----------------------

<b>Humidity</b>	Operation 30% - 85%, Storage 30% - 90%
-----------------	--

<b>Temperature</b>	Operation 5° C - 40° C, Storage -10° C - 50° C
--------------------	--

---

## Reliability

<b>Reliability</b>	7,000,000 MCBF (Lines), 180,000 MTBF (Hours)
--------------------	--

<b>Printer Life</b>	3,000,000 lines
---------------------	-----------------

<b>Ribbon life</b>	1,000,000 characters
--------------------	----------------------

<b>Print Head Life</b>	150 Mio Characters
------------------------	--------------------

---

## Standards Compliance

<b>EMC Standards</b>	CE marking
----------------------	------------

<b>Safety standards</b>	TÜV
-------------------------	-----

---

## Other Features

### **Sensors**

Top of Form sensor, Bottom of Form sensor

---

## What's in the box

### **What's in the box**

Main unit, Ribbon, User manual

---