Print method 7-pin shuttle impact dot matrix

Technology Serial Impact Dot Matrix

Fonts & Styles

Print Speed 1.90 ~ 2.30 lps

Column capacity slip 35 cps / 42 cps

Character size 1.6 mm (W) x 2.9 mm (H) / 1.3 mm (W) x 2.9 mm (H)

Character set 95 Alphanumeric, 32 International, 128 x 4 Graphic

Characters per inch 13.5 cpi / 16.2 cpi

Colour Printing Single Colour

Paper

Paper Types Slip

Copy capability slip two copies plus one original

Paper size slip 80 - 182 mm (W) x 69 - 257 mm (H)

Interfaces

Interfaces Drawer kick-out, Bidirectional parallel

Data Buffer

Data Buffer 512 Bytes or 35 Bytes

Power

Power Supply PS-180 (option)

General

Product dimensions 180 x 191 x 102 mm (Width x Depth x Height)

Product weight 1.6 kg

Colour Epson Dark Grey

Installation horizontally

Interface connectors D.K.D. function (2 drivers)

Noise Level Operation: 65 dB (A)

Humidity Operation 30% - 85%, Storage 30% - 90%

Temperature Operation 5° C - 40° C, Storage -10° C - 50° C

Reliability

Reliability 7,000,000 MCBF (Lines), 180,000 MTBF (Hours)

Printer Life 3,000,000 lines

Ribbon life 1,000,000 characters

Print Head Life 150 Mio Characters

Standards Compliance

EMC Standards CE marking

Safety standards TÜV

Other Features

Sensors

Top of Form sensor, Bottom of Form sensor

What's in the box

What's in the box

Main unit, Ribbon, User manual