
Print method	9-pin serial impact dot matrix
---------------------	--------------------------------

Technology	Serial Impact Dot Matrix
-------------------	--------------------------

Fonts & Styles

Print Speed	233 / 311 cps
--------------------	---------------

Column capacity slip	66 cps / 88 cps
-----------------------------	-----------------

Character size	1.6 mm (W) x 3.1 mm (H) / 1.3 mm (W) x 3.1 mm (H)
-----------------------	---

Character set	95 Alphanumeric, 37 International, 128 x 8 Graphic
----------------------	--

Characters per inch	16.7 cpi / 12.5 cpi
----------------------------	---------------------

Colour Printing	Single Colour
------------------------	---------------

Paper

Paper Types	Slip
--------------------	------

Copy capability slip	four copies plus one original
-----------------------------	-------------------------------

Paper size slip	70 - 210 mm (W) x 70 - 297 mm (H)
------------------------	-----------------------------------

Interfaces

Interfaces	RS-232, Drawer kick-out, Customer Display
-------------------	---

Power

Power Supply	PS-180 (option)
---------------------	-----------------

General

Product dimensions	252 x 205 x 185 mm (Width x Depth x Height)
Product weight	5 kg
Colour	Epson Cool White
Installation	horizontally
Interface connectors	D.K.D. function (2 drivers), Customer display port
Noise Level	Operation: 65 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -10° C - 50° C

Reliability

Reliability	29,000,000 MCBF (Lines), 180,000 MTBF (Hours)
Printer Life	12,000,000 lines
Ribbon life	4,500,000 characters
Print Head Life	200 Mio Characters

Standards Compliance

EMC Standards	CE marking
Safety standards	TÜV

Other Features

Changeable interface	Yes
-----------------------------	-----

Sensors

Cover Open Sensor, Top of Form sensor, Bottom of Form sensor

What's in the box

What's in the box

Main unit, Power switch cover, Ribbon, User manual
