Print method 9-pin serial impact dot matrix

Technology Serial Impact Dot Matrix

Fonts & Styles

Print Speed 4.70 lps (40 columns, 16.00 cpi)

Column capacity receipt Paper width 76 mm, 33 / 40

Character size 1.2 mm (W) x 3.1 mm (H) / 1.6 mm (W) x 3.1 mm (H)

Character set 95 Alphanumeric, 48 International, 128 x 12 Graphic

Characters per inch 13.3 cpi / 16 cpi

Paper

Paper Types Receipt

Copy capability receipt one copies plus one original

Paper size roll paper 76.00 ± 0.50 (W) mm x dia 83.00 mm,

 69.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces RS-232, Drawer kick-out

Power

Power Supply AC adapter, C

Operating Voltage 24 V

General

Product dimensions 160 x 248 x 139 mm (Width x Depth x Height)

Product weight 2.5 kg

Colour Epson Cool White

Installation horizontally, vertically with wall hanging bracket

Interface connectors D.K.D. function (2 drivers)

Noise Level Operation: 64 dB (A)

Humidity Operation 10% - 90%, Storage 10% - 90%

Temperature Storage -10° C - 50° C

Reliability

Reliability 18,000,000 MCBF (Lines), 180,000 MTBF (Hours)

Auto Cutter Life 800,000 Cuts

Printer Life 7,500,000 lines

Standards Compliance

EMC Standards CE marking

Safety standards TÜV

Other Features

Changeable interface Yes

Cutter Partial Cut

Sensors Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor

What's in the box

AC adapter, C, Main unit, Ribbon, Roll paper, User manual