

**Print type**

Print method	9-pin serial impact dot matrix
Technology	Serial Impact Dot Matrix

**Fonts & Styles**

Print Speed	4.70 lps (40 columns, 16.00 cpi )
Column capacity receipt	Paper width 76 mm, 33 / 40
Character size	1.2 mm (W) x 3.1 mm (H) / 1.6 mm (W) x 3.1 mm (H)
Character set	95 Alphanumeric, 48 International, 128 x 12 Graphic
Characters per inch	13.3 cpi / 16 cpi
Colour Printing	Two colours

**Paper**

Paper Types	Receipt
Copy capability receipt	one copies plus one original
Paper size roll paper	76.00 ± 0.50 (W) mm x dia 83.00 mm, 69.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm

**Interfaces**

Interfaces	Drawer kick-out, Bidirectional parallel
------------	--

**Power**

Power Supply	AC adapter, C
Operating Voltage	24 V

**General**

Product dimensions	160 x 248 x 139 mm (Width x Depth x Height)
Product weight	2.5 kg
Colour	Epson Dark Grey
Installation	horizontally, vertically with wall hanging bracket
Interface connectors	D.K.D. function (2 drivers)
Noise Level	Operation: 64 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Storage -10° C - 50° C

**Reliability**

Reliability	18,000,000 MCBF (Lines), 180,000 MTBF (Hours)
Auto Cutter Life	800,000 Cuts
Printer Life	7,500,000 Lines

**Standards Compliance**

EMC Standards	CE marking
---------------	------------

Safety standards	TÜV
------------------	-----

**Other Features**

Changeable interface	Yes
Cutter	Partial Cut
Sensors	Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor

**What's in the box**

What's in the box	AC adapter, C, Main unit, Ribbon, Roll paper, User manual
-------------------	---

**Other**

Warranty	12 months Carry in
----------	--------------------