

Print type

Print method	9-pin serial impact dot matrix
Technology	Serial Impact Dot Matrix

Fonts & Styles

Print Speed	4.70 lps (40 columns, 16.00 cpi)
Column capacity receipt	Paper width 76 mm, 33 / 40
Character size	1.2 mm (W) x 3.1 mm (H) / 1.6 mm (W) x 3.1 mm (H)
Character set	95 Alphanumeric, 48 International, 128 x 12 Graphic
Characters per inch	13.3 cpi / 16 cpi
Colour Printing	Two colours

Paper

Paper Types	Receipt
Copy capability receipt	one copies plus one original
Paper size roll paper	76.00 ± 0.50 (W) mm x dia 83.00 mm, 69.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces	Drawer kick-out, Bidirectional parallel
------------	--

Power

Power Supply	AC adapter, C
Operating Voltage	24 V

General

Product dimensions	160 x 248 x 139 mm (Width x Depth x Height)
Product weight	2.3 kg
Colour	Epson Dark Grey
Installation	horizontally, vertically with wall hanging bracket
Interface connectors	D.K.D. function (2 drivers)
Noise Level	Operation: 64 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Storage -10° C - 50° C

Reliability

Reliability	18,000,000 MCBF (Lines), 180,000 MTBF (Hours)
Printer Life	7,500,000 Lines

Standards Compliance

EMC Standards	CE marking
Safety standards	TÜV

Other Features

Changeable interface	Yes
Sensors	Roll paper cover open sensor, Paper End Sensor

What's in the box

What's in the box	AC adapter, C, Main unit, Ribbon, Roll paper, User manual
-------------------	---

Other

Warranty	12 months Carry in
----------	--------------------