

Model Name	TM-T88V
Print Method	Thermal line printing
Print Font	9 x17 / 12 x 24
Column Capacity (columns)	56 / 42
Character Size (mm)	0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H)
Character Set	95 Alphanumeric, 16set International, 128 × 43 Graphic Bar code: UPC-A, UPC-E, JAN8(EAN), JAN13(EAN), CODE39, CODE93, CODE128, ITF, CODABAR, GS1-128, GS1 DataBar Two-dimensional code: PDF417, QRCode, MaxiCode, 2D GS1 DataBar, Composite Symbology
Character Per Inch	20 CPI / 15 CPI
Interfaces	RS-232, Bi-directional parallel, USB, USB Plus Power, Ethernet(10/100 Base-T), Wireless LAN(IEEE802.11b)
Data Buffer	4K bytes / 45 bytes
Print Speed	Max. 300mm/sec
Paper Dimensions (mm)	Roll paper: 79.5 ± 0.5 (W) × dia. 83.0 / 57.5 ± 0.5 (W) × dia. 83.0
Paper Thickness (mm)	0.06 to 0.07
Power	24 VDC ± 7%
Power Consumption	Approx. 1.8 A (mean)
D.K.D. Function	2 drives
Reliability	
Printer Mechanism Life	20 million lines
Auto cutter life	2 million cuts (when using OJI Paper PD150R or PD160R)
MTBF	360,000 hours
MCBF	70,000,000 lines
Overall Dimensions (mm)	145 (W) x 195 (D) x 148 (H)
Mass (Approx)	1.6 kg
EMC Standards	FCC, VCCI, CE marking, AS / NZS CISPR22 class A GOST-R
Power Supply (option)	PS-180
Option	Wall-hanging bracket WH-10, Power supply box OT-BX88V
Safety Standards	UL / CSA / EN / TÜV / GOST-R
Optional power supply case secures cords under printer	Optional mounting bracket available for hanging the printer on the wall

