

---

<b>Print method</b>	Thermal line printing
---------------------	-----------------------

<b>Technology</b>	Thermal Line
-------------------	--------------

---

## Fonts & Styles

<b>Print Speed</b>	300 mm/sec
--------------------	------------

<b>Printing Font</b>	ANK
----------------------	-----

<b>Column capacity receipt</b>	Paper width 80 mm, 56 / 42
--------------------------------	----------------------------

<b>Character size</b>	0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)
-----------------------	--

<b>Character set</b>	95 Alphanumeric, 18 set International, 128 x 43 Graphic
----------------------	---

<b>Characters per inch</b>	20 cpi / 15 cpi
----------------------------	-----------------

<b>Dot density</b>	180 DPI x 180 DPI
--------------------	-------------------

<b>Colour Printing</b>	Black
------------------------	-------

<b>Printing Characters</b>	Text (incl. Euro symbol), Graphics, Barcode
----------------------------	---

---

## Paper

<b>Paper Types</b>	Receipt
--------------------	---------

<b>Paper size roll paper</b>	79.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm (option)
------------------------------	--

---

## Interfaces

<b>Interfaces</b>	USB 2.0 Type Mini-B, RS-232
-------------------	-----------------------------

---

## Data Buffer

<b>Data Buffer</b>	4 kB or 45 Bytes
--------------------	------------------

---

## Power

<b>Power Supply</b>	PS-180 & UK AC cable
<b>Power Consumption</b>	Standby: 0.1 A, Mean: 1.8 A
<b>Operating Voltage</b>	24 V

---

## General

<b>Product dimensions</b>	235 x 194 x 230 mm (Width x Depth x Height)
<b>Product weight</b>	2 kg
<b>Colour</b>	Black (EBCK)
<b>Installation</b>	horizontally, vertically, wall hanging
<b>Interface connectors</b>	D.K.D. function (2 drivers)
<b>Noise Level</b>	Operation: 55 dB (A)
<b>Humidity</b>	Operation 10% - 90%, Storage 10% - 90%
<b>Temperature</b>	Operation 4° C - 45° C, Storage -10° C - 50° C

---

## Reliability

<b>Reliability</b>	70,000,000 MCBF (Lines), 360,000 MTBF (Hours)
<b>Auto Cutter Life</b>	2,000,000 Cuts
<b>Printer Life</b>	20,000,000 lines
<b>Print Head Life</b>	150 km - 150,000,000 pulses

---

## Standards Compliance

**EMC Standards** CE marking, EN55022 Class A

**Safety standards** TÜV

---

## Other Features

**Changeable interface** Yes

**Cutter** Partial Cut

**Sensors** Paper End Sensor, Paper Near End Sensor, Cover Open Sensor

---

## What's in the box

**What's in the box** 58-mm width paper guide plate, Connector Cover, Main unit, Power switch cover, Roll paper, User manual, Warranty document

---