Print method Thermal line printing

Technology Themal Line

Fonts & Styles

Print Speed 300 mm/sec

Printing Font ANK

Column capacity receipt Paper width 80 mm, 56 / 42

Character size 0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)

Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic

Characters per inch 20 cpi / 15 cpi

Dot density 180 DPI x 180 DPI

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types Receipt

Paper size roll paper 79.50 \pm 0.50 (W) mm x dia 83.00 mm,

 57.50 ± 0.50 (W) mm x dia 83.00 mm (option)

Interfaces

Interfaces USB 2.0 Type Mini-B, RS-232

Data Buffer

Data Buffer

4 kB or 45 Bytes

Power

Power Supply PS-180 & UK AC cable

Power Consumption Standby: 0.1 A, Mean: 1.8 A

Operating Voltage 24 V

General

Product dimensions 145 x 195 x 148 mm (Width x Depth x Height)

Product weight 1.6 kg

Colour White (ENN8.5)

Installation horizontally, vertically, wall hanging

Interface connectors D.K.D. function (2 drivers)

Noise Level Operation: 55 dB (A)

Humidity Operation 10% - 90%, Storage 10% - 90%

Temperature Operation 4° C - 45° C, Storage -10° C - 50° C

Reliability

Reliability 70,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life 2,000,000 Cuts

Printer Life 20,000,000 lines

Print Head Life 150 km - 150,000,000 pulses

Standards Compliance

EMC Standards CE marking, EN55022 Class A

Safety standards TÜV

Other Features

Changeable interface Yes

Cutter Partial Cut

Sensors Paper End Sensor, Paper Near End Sensor, Cover Open Sensor

What's in the box

What's in the box 58-mm width paper guide plate, Connector Cover, Main unit, PS-180 & AC cable,

Power switch cover, Roll paper, User manual, Warranty document