

---

<b>Print method</b>	Thermal line printing
---------------------	-----------------------

<b>Technology</b>	Thermal Line
-------------------	--------------

---

## Fonts & Styles

<b>Print Speed</b>	250 mm/sec
--------------------	------------

<b>Character set</b>	95 Alphanumeric, 16 set International, 128 x 30 Graphic
----------------------	---

<b>Dot density</b>	203 DPI x 203 DPI
--------------------	-------------------

<b>Colour Printing</b>	Single Colour
------------------------	---------------

---

## Paper

<b>Paper Types</b>	Boarding pass
--------------------	---------------

<b>Paper size roll paper</b>	54.00 ± 0.50 (W) mm x dia 184.10 mm, 79.50 ± 0.50 (W) mm x dia 184.10 mm, 82.50 ± 0.50 (W) mm x dia 184.10 mm
------------------------------	---

---

## Interfaces

<b>Interfaces</b>	USB 2.0 Type B, RS-232
-------------------	------------------------

---

## Power

<b>Power Supply</b>	PS-180
---------------------	--------

<b>Operating Voltage</b>	24 V
--------------------------	------

---

## General

<b>Product weight</b>	2.8 kg
<b>Colour</b>	Epson Dark Grey
<b>Installation</b>	horizontally
<b>Noise Level</b>	Operation: 57 dB (A)
<b>Humidity</b>	Operation 10% - 80%, Storage 10% - 90%
<b>Temperature</b>	Operation 5° C - 45° C, Storage -20° C - 50° C

---

## Reliability

<b>Reliability</b>	360,000 MTBF (Hours)
<b>Auto Cutter Life</b>	100,000 Cuts
<b>Print Head Life</b>	100 km

---

## Standards Compliance

<b>EMC Standards</b>	CE marking
<b>Safety standards</b>	TÜV, GOST-R

---

## Other Features

<b>Cutter</b>	Full Cut
<b>Sensors</b>	Black Mark Sensor, Cover Open Sensor

---

## What's in the box

<b>What's in the box</b>	Main unit, PS-180, User manual
--------------------------	--------------------------------