Printing method	Thermal line printing	
Technology	Thermal line	
Fonts and styles		
Print speed	250 mm / s	
Character register	95 alphanumeric, 16 international, 128 × 30 graphic	
Point density	203 dpi x 203 dpi	
Color printing	Monochrome	
Paper		
Paper types	Luggage tag, boarding pass	
Paper format, roll paper	54.00 ± 0.50 (width) mm x diam. 184.10 mm, 79.50 ± 0.50 (width) mm x diam. 184.10 mm, 82.50 ± 0.50 (width) mm x diam. 184.10 mm	
Interfaces		
Interfaces	USB 2.0 type B, RS-232	
Switched on		
Power supply	PS-180	
Service voltage	24 V	

Weight	2.8 kg	
Color	Epson Dark Gray	
Installation	Horizontal	
Noise level	Operation: 57 dB (A)	
Air humidity	Operation 10% - 80%, storage 10% - 90%	
Temperature	Operation 5 ° C - 45 ° C, storage -20 ° C - 50 ° C	

Reliability

Reliability	360,000 MTBF (hours)
Auto-cutter service life	100,000 cuts
Print head life	100 km

According to standards

EMC standards	CE mark
Safety standards	TÜV, GOST-R

Other functions

Cutting unit	Total cut
Sensors	Black Mark Sensor, Open Cap Sensor

What is in the box

Others

Warranty

12 months Workshop repair