
Print method	Thermal line printing
---------------------	-----------------------

Technology	Thermal Line
-------------------	--------------

Fonts & Styles

Print Speed	250 mm/sec
--------------------	------------

Character set	95 Alphanumeric, 16 set International, 128 x 30 Graphic
----------------------	---

Dot density	203 DPI x 203 DPI
--------------------	-------------------

Colour Printing	Single Colour
------------------------	---------------

Paper

Paper Types	Boarding pass
--------------------	---------------

Paper size roll paper	54.00 ± 0.50 (W) mm x dia 184.10 mm, 79.50 ± 0.50 (W) mm x dia 184.10 mm, 82.50 ± 0.50 (W) mm x dia 184.10 mm
------------------------------	---

Interfaces

Interfaces	USB 2.0 Type B, RS-232
-------------------	------------------------

Power

Power Supply	PS-180
---------------------	--------

Operating Voltage	24 V
--------------------------	------

General

Product weight	2.8 kg
Colour	Epson Dark Grey
Installation	horizontally
Noise Level	Operation: 57 dB (A)
Humidity	Operation 10% - 80%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -20° C - 50° C

Reliability

Reliability	360,000 MTBF (Hours)
Auto Cutter Life	100,000 Cuts
Print Head Life	100 km

Standards Compliance

EMC Standards	CE marking
Safety standards	TÜV, GOST-R

Other Features

Cutter	Full Cut
Sensors	Black Mark Sensor, Cover Open Sensor

What's in the box

What's in the box	Main unit, PS-180, User manual
--------------------------	--------------------------------

Other

Warranty

12 months Carry-in
