printing method	Thermal Line Printing
Technique	thermal Printing
Fonts and Styles	
Print Speed	250mm / sec
Character Map	95 Alphanumeric, 16 International, 128 x 30 Graphics
dot Pitch	203 DPI x 203 DPI
color Printing	monochrome
Paper	
paper types	Baggage tag, Boarding pass
Paper form roll of paper	54.00 ± 0.50 (L) mm x diameter 184.10 mm, 79.50 ± 0.50 (L) mm x diameter. 184.10 mm,
	82.50 ± 0.50 (L) mm x diameter. 184.10 mm
interfaces	
Connections	USB 2.0 Type B, RS-232
Power	
network connector	PS-180
Operating voltage	24 V

Weight	2.8 kg
Color	Epson Dark Gray
Installation	horizontal
Noise level	Operation: 57 dB (A)
Humidity	Operation 10% - 80%, Storage 10% - 90%
Temperature	Operation 5 ° C - 45 ° C, Storage -20 ° C - 50 ° C

Reliability

Reliability	360,000 MTBF (hours)
Auto Cutter lifetime	100,000 Surgery
Print head life	100km

Compliance with standards

EMC standards	CE marking
safety Standards	TUV, GOST-R

additional Functions

cutting unit	Full Cut
sensors	Black Mark Sensor, Cover Open Sensor

What's in the box

Other

Warranty

12 Months Carry-in Warranty