

---

<b>Printing method</b>	Thermal printing of lines
------------------------	---------------------------

<b>Technology</b>	Thermoprint
-------------------	-------------

---

## Fonts and styles

<b>Print speed</b>	250 mm / sec
--------------------	--------------

<b>Character set</b>	95 alphanumeric, 16 international, 128 x 30 diagram
----------------------	---

<b>Point density</b>	203 dpi x 203 dpi
----------------------	-------------------

<b>Color printing</b>	A colour
-----------------------	----------

---

## Paper

<b>Type of paper</b>	Baggage tag, Boarding pass
----------------------	----------------------------

<b>Paper size paper roll</b>	54.00 ± 0.50 (W) mm x dia 184.10 mm, 79.50 ± 0.50 (W) mm x dia 184.10 mm, 82.50 ± 0.50 (W) mm x dia 184 , 10 mm
------------------------------	---

---

## Interfaces

<b>Connections</b>	USB 2.0 type B, RS-232
--------------------	------------------------

---

## Power

<b>Energy supply</b>	PS-180
----------------------	--------

<b>Operating voltage</b>	24 V
--------------------------	------

---

## General

<b>Dimensions</b>	156 x 236 x 147mm (Width x Depth x Height)
<b>Weight</b>	2.8 kg
<b>Color</b>	Epson Dark Gray
<b>Installation</b>	Horizontal
<b>Sound peak</b>	Operation: 57 dB (A)
<b>Humidity</b>	Operation 10% - 80%, Storage 10% - 90%
<b>Temperature</b>	Operation 5 ° C - 45 ° C, Storage -20 ° C - 50 ° C

---

## Reliability

<b>Reliability</b>	360,000 MTBF (hours)
<b>Cutter life</b>	100,000 cuts
<b>Printhead life</b>	100 km

---

## Compliance with standards

<b>EMC standards</b>	CE marking
<b>Safety standards</b>	TÜV, GOST-R

---

## Other functions

<b>Cutting device</b>	Cut completely
<b>Sensors</b>	Black Mark Sensor, Cover Open Sensor

---

## What's in the box

**Supplied accessories**

Main unit, PS-180, Owner's Manual

---

**Others**

**Guarantee**

12 months Carry-in

---