
Print method	Thermal line printing
---------------------	-----------------------

Print method receipt	Thermal line printing
-----------------------------	-----------------------

Technology	Thermal Line
-------------------	--------------

Fonts & Styles

Paper

Paper Types	Receipt
--------------------	---------

Paper size roll paper	79.50 ± 0.50 (W) mm x dia 83.00 mm
------------------------------	------------------------------------

Interfaces

Interfaces	USB 2.0 Type B, Wired Network, Drawer kick-out
-------------------	--

Data Buffer

Data Buffer	4 kB or 45 Bytes
--------------------	------------------

Power

Power Supply	PS-180 & UK AC cable
---------------------	----------------------

Power Consumption	Mean: 0.1 A
--------------------------	-------------

Operating Voltage	24 V
--------------------------	------

General

Product dimensions	125 x 194 x 114 mm (Width x Depth x Height)
Product weight	1.7 kg
Colour	Epson Cool White
Interface connectors	D.K.D. function
Noise Level	Operation: 55 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -10° C - 50° C

Reliability

Reliability	65,000,000 MCBF (Lines), 360,000 MTBF (Hours)
Auto Cutter Life	1,700,000 Cuts
Print Head Life	120 km - 120,000,000 pulses

Standards Compliance

EMC Standards	CE marking, GOST-R, EN55022 Class A
Safety standards	EN, TÜV, GOST-R

Other Features

Changeable interface	Yes
Cutter	Partial Cut

Other

Warranty

24 months Carry-in
