
Performance

Print technology	Thermal
Type	POS printer
Maximum resolution	180 x 180 DPI
Print speed	250 mm/sec

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	80 mm

Network

Ethernet LAN

Wi-Fi

Ports & interfaces

Connectivity technology	Wired
Standard interfaces	USB

USB port

Ports & interfaces

USB 2.0 ports quantity	1
USB connector	USB Type-B

Ports & interfaces

Bluetooth

Sound pressure level (printing)	55 dB
---------------------------------	-------

Features

Mean time between failures (MTBF)	360000 h
Country of origin	China

Certificates

Safety	EN, TÜV, GOST-R
Certification	CE, EN55022 Class A

Features

Product colour	Grey
----------------	------

Power

USB powered	
Power consumption	100 mA

Operational conditions

Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	125 mm
Depth	194 mm
Height	114 mm
Weight	1.7 kg

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Weight & dimensions

Package width	190 mm
Package depth	250 mm
Package height	240 mm
Package weight	2.2 kg

Print technology

Column capacity	80 mm, 56 / 42
-----------------	----------------

Logistics data

Quantity per pallet	112 pc(s)
Pallet length	120 cm
Pallet width	80 cm
Pallet height	181.6 cm
Quantity per pallet layer	16 pc(s)
Quantity per pallet layer (UK)	24 pc(s)
Quantity per pallet (UK)	168 pc(s)
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	181.6 cm

Other features

Dimensions (WxDxH)	125 x 194 x 114 mm
--------------------	--------------------

Memory

Buffer size	4 KB
Datasheet	Click here for datasheet