Print method Thermal line printing

Print method receipt Thermal line printing

Technology Themal Line

Fonts & Styles

Print Speed 250 mm/sec

Print Speed receipt 250 mm/sec

Printing Font ANK

Column capacity receipt Paper width 80 mm, 56 / 42

Character size 3.38 mm (H)

Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic

Characters per inch 20 cpi / 15 cpi

Dot density 180 DPI x 180 DPI

Colour Printing Black

Paper

Paper Types Receipt

Paper size roll paper 79.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces USB 2.0 Type B, Bluetooth, Drawer kick-out, RS-232

Data Buffer

Data Buffer 4 kB or 45 Bytes

Power

Power Supply PS-180 & UK AC cable

Power Consumption Mean: 0.1 A

Operating Voltage 24 V

General

Product dimensions 125 x 194 x 114 mm (Width x Depth x Height)

Product weight 2.17 kg

Colour Black (EBCK)

Interface connectors D.K.D. function

Noise Level Operation: 55 dB (A)

Humidity Operation 10% - 90%, Storage 10% - 90%

Temperature Operation 5° C - 45° C, Storage -10° C - 50° C

Reliability

Reliability 65,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life 1,700,000 Cuts

Print Head Life 120 km - 120,000,000 pulses

Standards Compliance

EMC Standards CE marking, GOST-R, EN55022 Class A

Safety standards EN, TÜV, GOST-R

Other Features

Changeable interface Yes

Cutter Partial Cut

What's in the box

What's in the box CD Manual, Main unit, PS-180 & AC cable, Power switch cover, Roll paper, Setup

guide, Warranty Documents