Print method	Thermal line printing
Print method receipt	Thermal line printing
Technology	Themal Line

Fonts & Styles

Print Speed	150 mm/sec
Print Speed receipt	150 mm/sec
Printing Font	ANK
Printing Font Receipt	ANK
Column capacity receipt	Paper width 58 mm, 35 / 42
Character size	0.88 mm (W) x 2.13 mm (H) / 1.25 mm (W) x 3 mm (H)
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	203 DPI x 203 DPI
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types	Receipt
Paper Thickness	48 mm - 80 mm
Paper size roll paper	57.50 ± 0.50 (W) mm x dia 18.00 mm, 57.50 ± 0.50 (W) mm x dia 60.00 mm

Interfaces

Data Buffer	64 kB or 128 Bytes
Power	
Power Supply	AC adapter, C, EURO AC cable
Power Consumption	Standby: 0.1 A, Mean: 1.5 A
General	
Product dimensions	102 x 102 x 102 mm (Width x Depth x Height)
Product weight	0.9 kg
Colour	White
Installation	horizontally, vertically
Interface connectors	D.K.D. function
Noise Level	Operation: 55 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -20° C - 60° C

Reliability

Reliability	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
Auto Cutter Life	1,000,000 Cuts
Printer Life	15,000,000 lines

Other Features

NFC	Near Field Communication available
Cutter	Partial Cut
Sensors	Paper End Sensor, Paper sensor
What's in the box	

What's in the box	AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Power switch cover, Roll
	paper, Setup guide, Warranty document