Print method Thermal line printing

Print method receipt Thermal line printing

Technology Themal Line

Fonts & Styles

Print Speed 150 mm/sec

Print Speed receipt 150 mm/sec

Printing Font ANK

Printing Font Receipt ANK

Column capacity receipt Paper width 58 mm, 35 / 42

Character size 0.88 mm (W) x 2.13 mm (H) / 1.25 mm (W) x 3 mm (H)

Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic

Dot density 203 DPI x 203 DPI

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types Receipt

Paper Thickness 48 mm - 80 mm

Paper size roll paper 57.50 ± 0.50 (W) mm x dia 18.00 mm,

57.50 ± 0.50 (W) mm x dia 60.00 mm

Interfaces

Interfaces USB 2.0 Type B, Drawer kick-out

Data Buffer

Data Buffer 64 kB or 128 Bytes

Power

Power Supply AC adapter, C, EURO AC cable

Power Consumption Standby: 0.1 A, Mean: 1.5 A

General

Product dimensions 102 x 102 x 102 mm (Width x Depth x Height)

Product weight 0.9 kg

Colour Black

Installation horizontally, vertically

Interface connectors D.K.D. function

Noise Level Operation: 55 dB (A)

Humidity Operation 10% - 90%, Storage 10% - 90%

Temperature Operation 5° C - 45° C, Storage -20° C - 60° C

Reliability

Reliability 60,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life 1,000,000 Cuts

Printer Life 15,000,000 lines

Other Features

NFC Near Field Communication available

Cutter Partial Cut

Sensors Paper End Sensor, Paper sensor

What's in the box

What's in the box AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Power switch cover, Roll

paper, Setup guide, Warranty document