Print method Thermal line printing

Technology Themal Line

Fonts & Styles

Print Speed 200 mm/sec

Print Speed receipt 200 mm/sec

Printing Font ANK

Printing Font Receipt ANK

Column capacity receipt Paper width 80 mm, 48 / 57

Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic

Dot density 203 DPI x 203 DPI

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types Receipt

Paper size 58 mm - 80 mm (Width)

Paper size roll paper 57.50 ± 0.50 (W) mm x dia 18.00 mm,

 57.50 ± 0.50 (W) mm x dia 83.00 mm, 79.50 ± 0.50 (W) mm x dia 18.00 mm, 79.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces Wired Network, Bluetooth, USB 2.0 Type B, USB 2.0 Type A, Drawer kick-out

Data Buffer

Data Buffer 12 kB

Power

Power Supply AC adapter, C, EURO AC cable

General

Product dimensions 127 x 127 mm (Width x Depth x Height)

Product weight 1.3 kg

Colour Black

Installation horizontally, vertically, wall hanging

Interface connectors D.K.D. function

Noise Level Operation: 55 dB (A)

Humidity Operation 10% - 90%, Storage 10% - 90%

Temperature Operation 5° C - 45° C, Storage -20° C - 60° C

Reliability

Reliability 60,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life 1,500,000 Cuts

Printer Life 15,000,000 lines

Print Head Life 100 km - 100,000,000 pulses

Other Features

NFC Near Field Communication available

Cutter Partial Cut

Sensors Paper End Sensor, Paper sensor

What's in the box

What's in the box AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Paper spacer, Power

switch cover, Roll paper, Setup guide, Warranty document

Other

Warranty 24 months Carry-in