Print method Thermal line printing

Print method receipt Thermal line printing

**Technology** Themal Line

# Fonts & Styles

Print Speed 150 mm/sec

Print Speed receipt 150 mm/sec

Printing Font ANK

Printing Font Receipt ANK

Column capacity receipt Paper width 58 mm, 35 / 42

**Character size** 0.88 mm (W) x 2.13 mm (H) / 1.25 mm (W) x 3 mm (H)

**Character set** 95 Alphanumeric, 18 set International, 128 x 43 Graphic

**Dot density** 203 DPI x 203 DPI

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

# Paper

Paper Types Receipt

Paper Thickness 48 mm - 80 mm

Paper size roll paper  $57.50 \pm 0.50$  (W) mm x dia 18.00 mm,

57.50 ± 0.50 (W) mm x dia 60.00 mm

#### Interfaces

**Interfaces** 

 ${\sf USB~2.0~Type~B,\,Drawer~kick-out,\,Wired~Network,\,USB~1.1~Type~A~(optional),\,USB}$ 

1.1 Type B (optional), USB 2.0 Type A (optional)

# Data Buffer

**Data Buffer** 64 kB or 128 Bytes

## Power

Power Supply AC adapter, C, EURO AC cable

**Power Consumption** Standby: 0.1 A, Mean: 1.5 A

#### General

**Product dimensions** 102 x 102 x 102 mm (Width x Depth x Height)

**Product weight** 0.9 kg

Colour Black

**Installation** horizontally, vertically

Interface connectors D.K.D. function

Noise Level Operation: 55 dB (A)

**Humidity** Operation 10% - 90%, Storage 10% - 90%

**Temperature** Operation 5° C - 45° C, Storage -20° C - 60° C

# Reliability

Reliability 60,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life 1,000,000 Cuts

Printer Life 15,000,000 lines

Print Head Life 100 km - 100,000,000 pulses

### Other Features

NFC Near Field Communication available

**Cutter** Partial Cut

Sensors Paper End Sensor, Paper sensor

### What's in the box

What's in the box AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Power switch cover, Roll

paper, Setup guide, Warranty document

### Other

**Warranty** 24 months Carry-in