
Print method

Thermal line printing

Technology

Thermal Line

Fonts & Styles

Print Speed

350 mm/sec

Print Speed (default)

300 mm/sec

Print Speed receipt

350 mm/sec

Printing Font

ANK

Column capacity receipt

Paper width 80 mm, 58 / 80

Character size

12 mm (W) x 24 mm (H) / 99 mm (W) x 24 mm (H)

Character set

95 Alphanumeric, 18 set International, 128 x 43 Graphic

Dot density

180 DPI x 180 DPI

Printing Characters

Text (incl. Euro symbol), Graphics, Barcode

Paper

Paper Types

Receipt

Paper Thickness

48 mm - 80 mm

Paper size roll paper

79.50 ± 0.50 (W) mm x dia 83.00 mm,

57.50 ± 0.50 (W) mm x dia 83.00 mm

Interfaces

Interfaces

USB 2.0 Type A, USB 2.0 Type B, RS-232, Wired Network, Wireless LAN IEEE 802.11b/g/n (WiFi 4) (optional), Wireless LAN IEEE 802.11a/b/g/n (optional), Drawer kick-out

Data Buffer

Data Buffer

4 kB or 45 Bytes

Power

Power Supply

PS-180 & EURO AC cable

Operating Voltage

24 V

General

Product dimensions

145 x 195 x 148 mm (Width x Depth x Height)

Product weight

1.6 kg

Colour

Black

Installation

horizontally, wall hanging

Interface connectors

D.K.D. function

Humidity

Operation 10% - 90%

Temperature

Operation 5° C - 45° C, Storage -10° C - 50° C

Reliability

Reliability

70,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life

3,000,000 Cuts

Printer Life

20,000,000 lines

Print Head Life

200 km - 200,000,000 pulses

Standards Compliance

EMC Standards

CE marking, EN55024

Safety standards

UL, CSA

Other Features

Changeable interface

Yes

NFC

Near Field Communication available

Cutter

Partial Cut

Sensors

Paper Near End Sensor, Cover Open Sensor, Paper sensor

What's in the box

What's in the box

Connector Cover, Main unit, PS-180 & AC cable, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document

Other

Warranty

48 months Carry-in
