

---

<b>Print method</b>	Thermal line printing
---------------------	-----------------------

<b>Technology</b>	Thermal Line
-------------------	--------------

---

## Fonts & Styles

<b>Print Speed</b>	350 mm/sec
--------------------	------------

<b>Print Speed (default)</b>	300 mm/sec
------------------------------	------------

<b>Print Speed receipt</b>	350 mm/sec
----------------------------	------------

<b>Printing Font</b>	ANK
----------------------	-----

<b>Column capacity receipt</b>	Paper width 80 mm, 58 / 80
--------------------------------	----------------------------

<b>Character size</b>	12 mm (W) x 24 mm (H) / 99 mm (W) x 24 mm (H)
-----------------------	---

<b>Character set</b>	95 Alphanumeric, 18 set International, 128 x 43 Graphic
----------------------	---

<b>Dot density</b>	180 DPI x 180 DPI
--------------------	-------------------

<b>Printing Characters</b>	Text (incl. Euro symbol), Graphics, Barcode
----------------------------	---

---

## Paper

<b>Paper Types</b>	Receipt
--------------------	---------

<b>Paper Thickness</b>	48 mm - 80 mm
------------------------	---------------

<b>Paper size roll paper</b>	79.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm
------------------------------	---

---

## Interfaces

<b>Interfaces</b>	USB 2.0 Type A, USB 2.0 Type B, RS-232, Wired Network, Wireless LAN IEEE 802.11b/g/n (WiFi 4) (optional), Wireless LAN IEEE 802.11a/b/g/n (optional), Drawer kick-out
-------------------	---

---

## Data Buffer

<b>Data Buffer</b>	4 kB or 45 Bytes
--------------------	------------------

---

## Power

<b>Power Supply</b>	PS-180 & UK AC cable
---------------------	----------------------

<b>Operating Voltage</b>	24 V
--------------------------	------

---

## General

<b>Product dimensions</b>	145 x 195 x 148 mm (Width x Depth x Height)
---------------------------	---

<b>Product weight</b>	1.6 kg
-----------------------	--------

<b>Colour</b>	Black
---------------	-------

<b>Installation</b>	horizontally, wall hanging
---------------------	----------------------------

<b>Interface connectors</b>	D.K.D. function
-----------------------------	-----------------

<b>Humidity</b>	Operation 10% - 90%
-----------------	---------------------

<b>Temperature</b>	Operation 5° C - 45° C, Storage -10° C - 50° C
--------------------	--

---

## Reliability

<b>Reliability</b>	70,000,000 MCBF (Lines), 360,000 MTBF (Hours)
--------------------	---

<b>Auto Cutter Life</b>	3,000,000 Cuts
-------------------------	----------------

<b>Printer Life</b>	20,000,000 lines
---------------------	------------------

<b>Print Head Life</b>	200 km - 200,000,000 pulses
------------------------	-----------------------------

---

## Standards Compliance

**EMC Standards** CE marking, EN55024

**Safety standards** UL, CSA

---

## Other Features

**Changeable interface** Yes

**NFC** Near Field Communication available

**Cutter** Partial Cut

**Sensors** Paper Near End Sensor, Cover Open Sensor, Paper sensor

---

## What's in the box

**What's in the box** Connector Cover, Main unit, PS-180 & AC cable, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document

---

## Other

**Warranty** 48 months Carry-in

---