**Print method** 

Thermal line printing

## Fonts & Styles

Print Speed 350 mm/sec

Printing Font ANK

Column capacity receipt Paper width 80 mm, 58 / 80

Character size 1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 2.4 mm (H)

**Character set** 95 Alphanumeric, 18 set International, 128 x 43 Graphic

**Dot density** 180 DPI x 180 DPI

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

## Paper

Paper Thickness 0.05 mm - 0.08 mm

Paper size roll paper  $79.50 \pm 0.50$  (W) mm x dia 83.00 mm,

57.50 ± 0.50 (W) mm x dia 83.00 mm

#### Interfaces

Interfaces USB 2.0 Type A (4x), USB 2.0 Type B, RS-232, Wired Network, Drawer kick-out

#### Power

Power Supply AC adapter, V

Operating Voltage 24 V

#### General

**Product dimensions** 145 x 195 x 148 mm (Width x Depth x Height)

**Product weight** 1.6 kg

**Installation** horizontally, vertically with wall hanging bracket

**Humidity** Operation 10% - 90%

**Temperature** Operation 5° C - 45° C

## Reliability

Reliability 70,000,000 MCBF (Lines), 350,000 MTBF (Hours)

Auto Cutter Life 3,000,000 Cuts

Printer Life 20,000,000 lines

**Print Head Life** 200 km - 200,000,000 pulses

# Standards Compliance

**EMC Standards** CE marking, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-

4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11

#### Other Features

NFC Near Field Communication available

CPU ARM Cortex-A5 384MHz

**Cutter** Partial Cut

Preloaded SW Device Data Notification, Print Data Notification, Server Direct Print, Web Server,

ePOS-Device®, ePOS-Display, ePOS-Print®

Sensors Paper Near End Sensor, Cover Open Sensor, Paper sensor

Storage 512MB NAND Flash

### What's in the box

What's in the box AC adapter, Connector Cover, EURO AC cable, Main unit, Paper guide, Power switch

cover, Roll paper, Setup guide, Warranty document