

---

<b>Print method</b>	Thermal line printing
---------------------	-----------------------

<b>Technology</b>	Thermal Line
-------------------	--------------

---

## Fonts & Styles

<b>Print Speed</b>	200 mm/sec
--------------------	------------

<b>Print Speed receipt</b>	200 mm/sec
----------------------------	------------

<b>Printing Font</b>	ANK
----------------------	-----

<b>Printing Font Receipt</b>	ANK
------------------------------	-----

<b>Column capacity receipt</b>	Paper width 80 mm, 48 / 57
--------------------------------	----------------------------

<b>Character set</b>	95 Alphanumeric, 18 set International, 128 x 43 Graphic
----------------------	---

<b>Dot density</b>	203 DPI x 203 DPI
--------------------	-------------------

<b>Printing Characters</b>	Text (incl. Euro symbol), Graphics, Barcode
----------------------------	---

---

## Paper

<b>Paper Types</b>	Receipt
--------------------	---------

<b>Paper size</b>	58 mm - 80 mm (Width)
-------------------	-----------------------

<b>Paper size roll paper</b>	57.50 ± 0.50 (W) mm x dia 18.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm, 79.50 ± 0.50 (W) mm x dia 18.00 mm, 79.50 ± 0.50 (W) mm x dia 83.00 mm
------------------------------	---

---

## Interfaces

<b>Interfaces</b>	Wired Network, Bluetooth, USB 2.0 Type B, USB 2.0 Type A, Drawer kick-out
-------------------	---

---

## Data Buffer

<b>Data Buffer</b>	12 kB
--------------------	-------

---

## Power

<b>Power Supply</b>	AC adapter, C, EURO AC cable
---------------------	------------------------------

---

## General

<b>Product dimensions</b>	127 x 127 x 127 mm (Width x Depth x Height)
---------------------------	---

<b>Product weight</b>	1.3 kg
-----------------------	--------

<b>Colour</b>	White
---------------	-------

<b>Installation</b>	horizontally, vertically, wall hanging
---------------------	--

<b>Interface connectors</b>	D.K.D. function
-----------------------------	-----------------

<b>Noise Level</b>	Operation: 55 dB (A)
--------------------	----------------------

<b>Humidity</b>	Operation 10% - 90%, Storage 10% - 90%
-----------------	--

<b>Temperature</b>	Operation 5° C - 45° C, Storage -20° C - 60° C
--------------------	--

---

## Reliability

<b>Reliability</b>	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
--------------------	---

<b>Auto Cutter Life</b>	1,500,000 Cuts
-------------------------	----------------

<b>Printer Life</b>	15,000,000 lines
---------------------	------------------

<b>Print Head Life</b>	100 km - 100,000,000 pulses
------------------------	-----------------------------

---

## Other Features

<b>NFC</b>	Near Field Communication available
<b>Cutter</b>	Partial Cut
<b>Sensors</b>	Paper End Sensor, Paper sensor

---

## What's in the box

<b>What's in the box</b>	AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document
--------------------------	--

---