Print method	Thermal line printing
Technology	Themal Line
Fonts & Styles	
Print Speed	200 mm/sec
Print Speed receipt	200 mm/sec
Printing Font	ANK
Printing Font Receipt	ANK
Column capacity receipt	Paper width 80 mm, 48 / 57
Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density	203 DPI x 203 DPI
Printing Characters	Text (incl. Euro symbol), Graphics, Barcode

## Paper

Paper Types	Receipt
Paper size	58 mm - 80 mm (Width)
Paper size roll paper	57.50 ± 0.50 (W) mm x dia 18.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm, 79.50 ± 0.50 (W) mm x dia 18.00 mm, 79.50 ± 0.50 (W) mm x dia 83.00 mm

## Interfaces

Interfaces

Wired Network, Drawer kick-out, USB 2.0 Type A, Bluetooth

**Tablet Charge** 

Data Buffer	
Data Buffer	12 kB
Power	
Power Supply	PS-180, EURO AC cable
General	
Product dimensions	127 x 127 x 127 mm (Width x Depth x Height)
Product weight	1.3 kg
Colour	White
Installation	horizontally, vertically, wall hanging
Interface connectors	D.K.D. function
Noise Level	Operation: 55 dB (A)
Humidity	Operation 10% - 90%, Storage 10% - 90%
Temperature	Operation 5° C - 45° C, Storage -20° C - 60° C
Reliability	
Reliability	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)

Auto Cutter Life	1,500,000 Cuts
Printer Life	15,000,000 lines

Print Head Life 100 km - 100,000,000 pulses

## Other Features

NFC	Near Field Communication available
Cutter	Partial Cut
Sensors	Paper End Sensor, Paper sensor
What's in the box	
What's in the box	AC adapter, C1, AC cable, Cable fixation saddle, Main unit, Paper spacer, Power switch cover, Roll paper, Setup guide, Warranty document