

---

<b>Print method</b>	Thermal line printing
---------------------	-----------------------

<b>Technology</b>	Thermal Line
-------------------	--------------

---

## Fonts & Styles

<b>Print Speed</b>	250 mm/sec
--------------------	------------

<b>Print Speed receipt</b>	250 mm/sec
----------------------------	------------

<b>Printing Font</b>	ANK
----------------------	-----

<b>Column capacity receipt</b>	Paper width 80 mm, 48 / 64
--------------------------------	----------------------------

<b>Character set</b>	95 Alphanumeric, 18 set International, 128 x 43 Graphic
----------------------	---

<b>Characters per inch</b>	22.6 cpi / 16.9 cpi
----------------------------	---------------------

<b>Dot density</b>	203 DPI x 203 DPI
--------------------	-------------------

<b>Colour Printing</b>	Black
------------------------	-------

<b>Printing Characters</b>	Text (incl. Euro symbol), Graphics, Barcode
----------------------------	---

---

## Paper

<b>Paper Types</b>	Receipt
--------------------	---------

<b>Paper size roll paper</b>	79.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm
------------------------------	---

---

## Interfaces

<b>Interfaces</b>	Wired Network, Drawer kick-out
-------------------	--------------------------------

---

## Data Buffer

<b>Data Buffer</b>	4 kB or 45 Bytes
--------------------	------------------

---

## Power

<b>Power Supply</b>	AC adapter, C1
<b>Power Consumption</b>	Standby: 0.1 A, Mean: 1.8 A
<b>Operating Voltage</b>	24 V

---

## General

<b>Product dimensions</b>	140 x 199 x 146 mm (Width x Depth x Height)
<b>Product weight</b>	1.7 kg
<b>Colour</b>	Black (EBCK)
<b>Installation</b>	horizontally, vertically, vertically with wall hanging bracket
<b>Interface connectors</b>	D.K.D. function (2 drivers)
<b>Noise Level</b>	Operation: 55 dB (A)
<b>Humidity</b>	Operation 10% - 90%, Storage 10% - 90%
<b>Temperature</b>	Operation 5° C - 45° C, Storage -10° C - 50° C

---

## Reliability

<b>Reliability</b>	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
<b>Auto Cutter Life</b>	1,500,000 Cuts
<b>Printer Life</b>	15,000,000 lines
<b>Print Head Life</b>	150 km - 150,000,000 pulses

---

## Standards Compliance

**EMC Standards** FCC class A, CE marking, EN55022 Class A

**Safety standards** UL, CSA, TÜV

---

## Other Features

**Cutter** Partial Cut

**Sensors** Paper End Sensor, Paper Near End Sensor

**Paper Saving Function** Yes

---

## What's in the box

**What's in the box** AC adapter, C1, CD Manual, EURO AC cable, Main unit, Paper roll spacer, Power switch cover, Roll paper, Rubber feet, Setup guide, Wall hanging bracket, Warranty document

---