
Print method	Thermal line printing
---------------------	-----------------------

Technology	Thermal Line
-------------------	--------------

Fonts & Styles

Print Speed	250 mm/sec
--------------------	------------

Print Speed receipt	250 mm/sec
----------------------------	------------

Printing Font	ANK
----------------------	-----

Column capacity receipt	Paper width 80 mm, 48 / 64
--------------------------------	----------------------------

Character set	95 Alphanumeric, 18 set International, 128 x 43 Graphic
----------------------	---------------------------------------------------------

Characters per inch	22.6 cpi / 16.9 cpi
----------------------------	---------------------

Dot density	203 DPI x 203 DPI
--------------------	-------------------

Colour Printing	Black
------------------------	-------

Printing Characters	Text (incl. Euro symbol), Graphics, Barcode
----------------------------	---------------------------------------------

Paper

Paper Types	Receipt
--------------------	---------

Paper size roll paper	79.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm
------------------------------	---------------------------------------------------------------------------

Interfaces

Interfaces	Wired Network, Drawer kick-out
-------------------	--------------------------------

Data Buffer

Data Buffer	4 kB or 45 Bytes
--------------------	------------------

Power

Power Supply	AC adapter, C1, UK AC cable
---------------------	-----------------------------

Power Consumption	Standby: 0.1 A, Mean: 1.8 A
--------------------------	-----------------------------

Operating Voltage	24 V
--------------------------	------

General

Product dimensions	140 x 199 x 146 mm (Width x Depth x Height)
---------------------------	---------------------------------------------

Product weight	1.7 kg
-----------------------	--------

Colour	Black (EBCK)
---------------	--------------

Installation	horizontally, vertically, vertically with wall hanging bracket
---------------------	----------------------------------------------------------------

Interface connectors	D.K.D. function (2 drivers)
-----------------------------	-----------------------------

Noise Level	Operation: 55 dB (A)
--------------------	----------------------

Humidity	Operation 10% - 90%, Storage 10% - 90%
-----------------	----------------------------------------

Temperature	Operation 5° C - 45° C, Storage -10° C - 50° C
--------------------	------------------------------------------------

Reliability

Reliability	60,000,000 MCBF (Lines), 360,000 MTBF (Hours)
--------------------	-----------------------------------------------

Auto Cutter Life	1,500,000 Cuts
-------------------------	----------------

Printer Life	15,000,000 lines
---------------------	------------------

Print Head Life	150 km - 150,000,000 pulses
------------------------	-----------------------------

Standards Compliance

EMC Standards FCC class A, CE marking, EN55022 Class A

Safety standards UL, CSA, TÜV

Other Features

Cutter Partial Cut

Sensors Roll paper cover open sensor, Paper End Sensor

Paper Saving Function Yes

What's in the box

What's in the box AC adapter, C1, CD Manual, Main unit, Paper roll spacer, Power switch cover, Roll paper, Rubber feet, Setup guide, UK AC cable, Wall hanging bracket, Warranty document
