

Soundcraft LX7ii Specs

Total # Of Inputs	32 - Total Line Inputs
Mic/Line Inputs	32 - Balanced 1/4" TRS Phone Inputs 32 - Balanced XLR Mic Inputs
Stereo Line Inputs	2 - L/R Stereo Paired 1/4" TRS Phone
In-Line Inputs>Returns	No
AUX Sends	6 - 1/4" TRS Phone
AUX Returns	2 - L/R Stereo Paired 1/4" TRS Phone)
Inserts	No
BUS (Group) Outputs	AUX Outputs: 6 - 1/4" TRS Phone
2 Trk Master I/O	Main Outputs: L/R Balanced 3-pin XLR male
ALT I/O	Monitor Output: L/R 1/4" TRS Phone 2 Trk Input: L/R RCA Phono jacks
Monitor Outputs	Monitor Output: L/R 1/4" TRS Phone
EQ Section	100Hz, 18dB per octave

HF: 12kHz, +/-15dB, 2nd order shelving
Hi-Mid: 550Hz-13kHz, +/-15dB, Q=1
Lo-Mid: 80Hz-1.9kHz, +/-15dB, Q=1
LF: 80Hz, +/-15dB 2nd order shelving

Solo/Mute Mute & Solo on all channels

Channel Level Control 100mm Faders

Trim/Gain Control Sealed Rotary Potentiometers

Phantom Power +48 Volt

Metering 12-segment multicolored LED: Group Masters, L/R Master sections
AFL/PFL LED indicator

Frequency Response XLR input to any output:
20Hz to 20kHz, +0/-1dB

Dynamic Range *not specified by manufacturer*

Signal-to-Noise Ratio < -128dBu (150 Ohm source)
22Hz - 22kHz bandwidth,
unweighted

Total Harmonic Distortion (THD) *All measurements at +10dBu output
30dB gain*
XLR Input to Direct Output: <0.007%
@ 1kHz
XLR Input to Mix Output: <0.008% @
1kHz

Power Supply Universal Mains input 85V-270V AC,

50Hz/60Hz
Power Consumption - less than 50W

Dimensions 41.4 x 6.5 x 19.8" (1059 x 164 x 503mm) (WxHxD)

Weight 50lbs (23kg)

Packaging Info

Package Weight 56.6 lb

Box Dimensions (LxWxH) 45 x 25 x 12"
