

Soundcraft Signature 10 Specs

Frequency Response	Mic / Line In to Any Output: 20 Hz to 20 kHz (± 1.5 dB)
THD	Mono Mic Sensitivity -30 dBu, Input Level -16 dBu, +14 dBu @ Mix Output: < 0.002% @ 1 kHz Stereo Mic Sensitivity -30 dBu, Input Level -16 dBu, +14 dBu @ Mix Output: < 0.007% 1 kHz
Noise	Mono Mic Input E.I.N. (Max Gain): < -126 dBu (150 Ohm source) Stereo Mic Input E.I.N. (Max Gain): < -124 dBu (150 Ohm source)
Crosstalk @ 1 kHz	Channel Mute: > -90 dB Fader Cut-off (rel +10 mark): > -90 dB Aux Send Pots Offness: > -82 dB
EQ Section	EQ (Mono Inputs) HF: 12 kHz, ± 15 dB MF (swept): 140 Hz to 3 kHz, ± 15 dB LF: 60 Hz, ± 15 dB EQ (Stereo Inputs) HF: 12 kHz, ± 15 dB MF: 1 kHz, ± 15 dB LF: 60 Hz, ± 15 dB
Input & Output	Input and Output Levels Mic Input: +12.5 dBu max Line Input: > +26 dBu max Stereo Inputs: > +26 dBu max

Mix Output: +21.5 dBu max
Headphones (@ 150 Ohms): 300 mW

Impedance Input & Output Impedance
Mic Input: 1.2 kOhms
Hi-Z Input: 968 kOhms
Line Input: 10 kOhms
Stereo Input: 21.5 kOhms
Outputs: 150 Ohms (balanced), 75
Ohms (unbalanced)

USB Audio Inputs/Outputs: 2-in, 2-out
Bit Depth: 16-bit, 24-bit
Sampling Rate: 44.1 / 48 / 88.2 / 96 /
176.4 / 192 kHz

Power Consumption <50 VA

Operating Temperature 41 to 104°F / 5 to 40°C

Dimensions 19.3 x 15.0 x 8.3" / 490.0 x 380.0 x
210.0 mm

Weight 10.9 lb / 5.0 kg

Packaging Info

Package Weight 13.25 lb

Box Dimensions (LxWxH) 19.3 x 15.2 x 8.3"
