

AKG SST4500 Specs

| | |
|-----------------------|---|
| Frequency Range | 570.1-600.5MHz |
| Switching Bandwidth | <= 30.5MHz (country-dependent) |
| Audio Bandwidth | 35Hz-20MHz (\pm 3 dB) |
| THD | <0.5% typ. |
| Signal to Noise Ratio | >90 dB(A) typ. |
| Modulation | FM, MPX stereo |
| Audio Inputs | 2 x XLR / jack hybrid socket (balanced XLR, unbalanced TS 1/4" jack) |
| Audio Outputs | 2 x loop TS 1/4" jack sockets unbalanced 1 x line TS 1/4" jack sockets balanced 1 x TS 1/4" jack sockets balanced (headphones) |
| RF Output Power | 100mW |
| Certifications | Remaining battery life (Patent no. AT 408.280, GB 2.349.230, US 6,344,730), Method of Simulating Sound Impression (Patent no. EP 641.143 (DE, DK, FI, FR, GB, IT, NL), JP 3.565.908, US 5.544.249), Stereo Multiplex Encoder (Patent no. ZL 0211301956) |

Dimensions

1/2 19" (482.6mm) 1U rack, 7.8 x 1.7 x 8.5" (200 x 44 x 216mm)

Weight

2.4 lb. (1.1kg)
