

# AKG WMS40 MINI Specs

## Transmitter

---

Frequency Bandwidth	B & D
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion (THD)	0.8% @ 1 kHz
Peak Deviation	45 kHz
Nominal Deviation	15 kHz
Radio Output Power	10 mW
Transmitter Synchronization	Manual
Audio Input	3-pin mini XLR-F
Number of Selectable Frequencies	1 fixed frequency
Range	66' / 20 m
Modulation	FM

---

Pilot Tone	No
Encryption	No
Maximum Audio Level	12 dB
Battery	1 x LR6 AA alkaline
Operating Time	30 hours
Material of Construction	Plastic
Dimensions (L x H x W)	2.4 x 3.0 x 1.2" / 60 x 75.5 x 30 mm
Weight	Not specified by manufacturer

## Receiver

---

Frequency Bandwidth	B & D
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion	0.8% @ 1 kHz
Radio Sensitivity	-100 dBm
Channels	2
Number of Selectable	1 fixed frequency for each channel



---

Dimensions (L x H x W)

5.2 x 1.7 x 5.2" / 132 x 43 x 133 mm

---

Weight

1.3 lb / 581 g

---