

sr45 TECHNICAL SPECIFICATION

Audio	Audio frequency bandwidth		40 to 20000 Hz
	Signal to Noise		105 dB-A
	THD at 1 kHz		0.8 Prozent
Enhanced	Operating temperature range		-10 to 55 Celsius
	Radio Sensitivity		-100 dBm
	Switching bandwidth		30 MHz
	Recommended simultaneous channels		5
	Number of selectable frequencies		8 Fixed frequencies
	Frequency selection		Fixed frequency
Radio	Wireless channels within device		-
	Radio Range (Line of Sight)		30m
	Switchable RF Power		no
	Modulation		FM
	Encryption		No encryption
	Pilot tone		no
	Transmitter Synchronization		Manual
General	HiQnet compatible		No
	Racksize		1/2 Racksize (19 ")
	Rackheight		1 RU
	Amount	1	
	Type	Balanced XLR	
Audio Outputs 1	Gender	Male	
	Contacts	3-pin	
	Note	Balanced audio output adjustable from mic to line level. Output level at rated deviation: 500 mV rms	
	Amount	1	
Audio Outputs 2	Type	Jack Mono (1/4 ")	
	Contacts	3-pin	
	Note	Unbalanced audio output	
	Internal Power Supply		no
Powering interface	Type		DC Socket
	Voltage		12 to 12 V
Design	Body	Plastic	
	Finish	black	
	Length	150 mm	
Dimensions / Weight	Height	44 mm	
	Width	200 mm	