

## SR 45

- Carrier frequency range: 500 - 865 MHz
- Audio bandwidth: 40 - 20,000 Hz
- THD: typ. 0,8 % (at 1 kHz)
- Signal/noise ratio: typ. 105 dB(A)
- Modulation: FM
- Audio outputs: Balanced XLR and unbalanced 1/4" (6.3 mm) jack: adjustable from mic to line level. Output level at rated deviation: 500 mV rms
- Squelch threshold: -100 to -70 dBm adjustable
- Dimensions: Width: 200 mm (7.9 in.); height: 44 mm (1.7 in.); depth: 150 mm (5.9 in.)

## PT 45

- Carrier frequency range: 500 - 865 MHz
- Audio bandwidth: 40 - 20,000 Hz
- THD: typ. 0,8 % (at 1 kHz)
- Signal/noise ratio: typ. 105 dB(A)
- Modulation: FM
- RF radiation: 10 mW
- Power supply: 1x 1.5 V AA size battery
- Battery life: 10 hours typ.
- Dimensions: Width: 60 mm (2.4 in.); height: 74 mm (2.9 in.); depth: 30 mm (1.2 in.)

## CK 99-L

- Polar pattern: Cardioid
- Frequency range: 15 to 18,000 Hz
- Sensitivity: 8.8 mV/Pa (-41 dBV)
- Max. SPL: 118 dB (k=1 %)
- Equivalent noise level: 34 dB-A
- Signal/noise ratio (A-weighted): 60 dB
- Impedance: 200 ohms
- Recommended load impedance: >2000 ohms
- Supply voltage: 1.5 to 10 VDC or 9 to 52 V phantom power to IEC 61938 using MPA V L
- Powering:
- Connector: 3-pin mini XLR
- Cable: 1.6 m (5 ft. 4 in.)
- Finish: matte black