AKG HT45 BD M Specifications

AUDIO

Audio Frequency bandwidth: 70 to 20000 Hz Signal to Noise: 105 dB-A THD at 1 kHz: 0.8 Prozent **ENHANCED** -10 to 55 Celsius Operating temperature range: Peak deviation: 45 kHz **RADIO** Switching bandwidth: 30 MHz Recommended simultaneous channels: 5 Number of selectable frequencies: 8 Fixed frequencies Frequency Selection: Fixed frequency Radio Range (Line of Sight): 30m Switchable RF Power: no Modulation: FΜ **Encryption:** No encryption **Pilot Tone:** no **TRANSMITTER** Nominal deviation: 15 kHz 0 ... 0 mW Radio Output Power (min/max): P5 Microphone head versions: Interchangeable Microphone Head: no **Transmitter Synchronization:** Manual **BATTERY 1** LR6 AA alkaline battery Batterytype: **Number of Batteries:** 1 **Operating Time:** 7 h

BATTERY 2

Batterytype: HR 6 AA (NiHM) rechargeable battery

	Number of Batteries:	1	
	Operating Time:	8 h	
BATTERY 3			
	Batterytype:	HR 6 AA (NiHM) rechargeable battery	
	Number of Batteries:	1	
	Operating Time:	8 h	
DESIGN			
	Body:	Plastic	
	Finish:	black	
DIMENSIONS / WEIGHT			
	Height:		237 mm
	Width:		51 mm
	Net Weight:		214 g