

AUDIO

Audio Frequency bandwidth:	40 to 20000 Hz
Signal to Noise:	105 dB-A
THD at 1 kHz:	0.8 Prozent

ENHANCED

Operating temperature range:	-10 to 55 Celsius
Radio Sensitivity:	-100 dBm

RADIO

Switching bandwidth:	30 MHz
Recommended simultaneous channels:	5
Number of selectable frequencies:	8 Fixed frequencies
Frequency Selection:	Fixed frequency
Radio Range (Line of Sight):	30m
Switchable RF Power:	no
Modulation:	FM
Encryption:	No encryption
Pilot Tone:	no

GENERAL

Transmitter Synchronization:	Manual
HiQnet compatible:	No
Racksize:	1/2 Racksize (19")
Rackheight:	1 RU

AUDIO OUTPUTS 1

Amount: 1

Type: Balanced XLR

Gender: Male

Contacts:3-pin

Note: Balanced audio output adjustable from mic to line level. Output level at rated deviation: 500 mV rms

AUDIO OUTPUTS 2

Amount: 1
Type: Jack Mono (1/4")
Contacts: 3-pin
Note: Unbalanced audio output

POWERING INTERFACE

Internal Power Supply: nonein
Type: DC Socket
Voltage: 12 to 12 V

DESIGN

Body: Plastic
Finish: black

DIMENSIONS / WEIGHT

Length: 150 mm

Height: 44 mm

Width: 200 mm

SKU 3245H00110