

Transmitter

Audio Frequency Response	40 to 20 kHz
--------------------------	--------------

Signal to Noise	110 dBA
-----------------	---------

Total Harmonic Distortion (THD)	0.8 % @ 1 kHz
---------------------------------	---------------

Peak Deviation	45 kHz
----------------	--------

Nominal Deviation	15 kHz
-------------------	--------

Radio Output Power	10 mW
--------------------	-------

Transmitter Synchronization	Manual
-----------------------------	--------

Audio Input	3-pin mini XLR-F
-------------	------------------

Channels	3
----------	---

Number of Selectable Frequencies	1 fixed frequency
----------------------------------	-------------------

Range	66' (20 m)
-------	------------

Modulation	FM
------------	----

Pilot Tone	No
------------	----

Encryption	No
------------	----

Maximum Audio Level	12 dB
Battery	1 x LR6 AA alkaline
Operating Time	30 hours
Material of Construction	Plastic
Dimensions (L x H x W)	2.4 x 3.0 x 1.2" (60 x 75.5 x 30 mm)
Weight	Not specified by manufacturer

Receiver

Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion	0.8% @ 1 kHz
Operating Temperature Range	14 to 131°F (-10 to 55°C)
Radio Sensitivity	-100 dBm
Channels	3
Number of Selectable Frequencies	1 fixed frequency
Frequency Selection	Fixed

Range	66' (20 m)
Modulation	FM
Encryption	No
Pilot Tone	No
Transmitter Synchronization	Not necessary
HiQnet Compatible	No
Rack Compatibility	1/3 rack size (19") Rack height: 1 RU
Antenna	1 x fixed external antenna
Audio Output	1 x balanced TRS 1/4" (6.3 mm) female jack Balanced audio output adjustable from mic to line level Output level at rated deviation: 500 mV rms
Internal Power Supply	No Type: DC socket Voltage: 12 V
Material of Construction	Metal
Dimensions (L x H x W)	5.2 x 1.7 x 5.2" (132 x 43 x 133 mm)

Packaging Info

Package Weight 2.5 lb

Box Dimensions (LxWxH) 11.7 x 9.5 x 2.6"
