

# Transmitter

---

Frequency Bandwidth	Band B
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion (THD)	0.8 % @ 1 kHz
Operating Temperature Range	14 to 131°F (-10 to 55°C)
Peak Deviation	45 kHz
Nominal Deviation	15 kHz
Radio Output Power	10 mW
Transmitter Synchronization	Manual
Interchangeable Mic Heads	No
Channels	3
Number of Selectable Frequencies	1 fixed frequency
Range	66' (20 m)

Modulation	FM
Pilot Tone	No
Encryption	No
Battery	1 x LR6 AA alkaline
Operating Time	30 hours
Material of Construction	Plastic
Dimensions (H x W)	9.1 x 2.0" (230 x 51 mm)
Weight	6.9 oz (195 g)

## Receiver

---

Frequency Bandwidth	Band B
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion	0.8% @ 1 kHz
Operating Temperature Range	14 to 131°F (-10 to 55°C)
Radio Sensitivity	-100 dBm

Channels	3
Number of Selectable Frequencies	1 fixed frequency
Frequency Selection	Fixed
Range	66' (20 m)
Modulation	FM
Encryption	No
Pilot Tone	No
Transmitter Synchronization	Not necessary
HiQnet Compatible	No
Rack Compatibility	1/3 rack size (19") Rack height: 1 RU
Antenna	1 x fixed external antenna
Audio Output	1 x balanced TRS 1/4" (6.3 mm) female jack Balanced audio output adjustable from mic to line level Output level at rated deviation: 500 mV rms
Internal Power Supply	No Type: DC socket Voltage: 12 V

Material of Construction	Metal
--------------------------	-------

---

Dimensions (L x H x W)	5.2 x 1.7 x 5.2" (132 x 43 x 133 mm)
------------------------	--------------------------------------

---

## Packaging Info

---

Package Weight	2.55 lb
----------------	---------

---

Box Dimensions (LxWxH)	11.8 x 9.55 x 2.45"
------------------------	---------------------

---