

AKG WMS40 MINI Specs

Transmitter

Frequency Bandwidth	B & D
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion (THD)	0.8% @ 1 kHz
Peak Deviation	45 kHz
Nominal Deviation	15 kHz
Radio Output Power	10 mW
Transmitter Synchronization	Manual
Interchangeable Mic Heads	No
Number of Selectable Frequencies	1 fixed frequency
Range	66' / 20 m
Modulation	FM

Pilot Tone	No
Encryption	No
Battery	1 x LR6 AA alkaline
Operating Time	30 hours
Material of Construction	Plastic
Operating Temperature Range	14 to 131°F / -10 to 55°C
Dimensions (H x W)	9.1 x 2.0" / 230 x 51 mm
Weight	6.9 oz / 195 g

Receiver

Frequency Bandwidth	B & D
Audio Frequency Response	40 to 20 kHz
Signal to Noise	110 dBA
Total Harmonic Distortion	0.8% @ 1 kHz
Radio Sensitivity	-100 dBm
Channels	2

Number of Selectable Frequencies	1 fixed frequency
Frequency Selection	Fixed
Range	66' / 20 m
Modulation	FM
Encryption	No
Pilot Tone	No
Transmitter Synchronization	Not necessary
HiQnet Compatible	No
Rack Compatibility	1/3 rack size (19") Rack Height: 1 RU
Antenna	2 x fixed external antennas
Audio Output	2 x balanced TRS 1/4" (6.3 mm) female jack Balanced audio output adjustable from mic to line level Output Level at Rated Deviation: 500 mV rms
Power Supply	Type: DC socket Voltage: 12 VDC
Material of Construction	Metal

Operating Temperature Range	14 to 131°F / -10 to 55°C
-----------------------------	---------------------------

Dimensions (L x H x W)	5.2 x 1.7 x 5.2" / 132 x 43 x 133 mm
------------------------	--------------------------------------

Weight	1.3 lb / 581 g
--------	----------------

Packaging Info

Package Weight	3.3 lb
----------------	--------

Box Dimensions (LxWxH)	11.5 x 11.3 x 2.6"
------------------------	--------------------
