

# AKG C417 Specs

Transducer	<i>Pre-Polarized Condenser</i>
Polar Pattern	Omnidirectional
Frequency Response	20 Hz - 20 kHz
Dynamic Range (Typical)	<i>Not Specified by Manufacturer</i>
Signal-to-Noise Ratio	60 dB (A-Weighted)
Maximum Input Sound Level	118 dB @ 1kHz, (for 3% THD: 126 dB)
Power Requirements	Power is Provided by Wireless Transmitter
Output Impedance	200 Ohms
Output Connectors	3-Pin Miniature XLR <i>for Use with Wireless Systems</i>
Case	<i>Not Specified by Manufacturer</i>
Pad	None
Low Frequency Roll-Off	None

Applications	Radio, Videography, Television and Broadcast.
--------------	---

---

Dimensions	Microphone: .06 x .3" (15 x 7.5mm) LxW Cable: 5' (1.5 m) Cable Terminated in a Mini-XLR Connector for Use With AKG Wireless Systems
------------	---

---

Weight	0.3 oz. (8.0 g)
--------	-----------------

---

## Packaging Info

---

Package Weight	0.5 lb
----------------	--------

---

Box Dimensions (LxWxH)	6.6 x 5 x 2.5"
------------------------	----------------

---