

Item# 3300H00220

General Specifications

Switching bandwidth30.5 MHz (depending on local regulations)

ModulationFM

Sensitivity6 dB $\mu$ V / -100 dBm

Receiver typeSuper heterodyne

Diversity system $\mu$ C controlled space diversity

Audio bandwidth35 to 20,000 Hz

THD at 1 kHz<0.3%

Signal-to-noise120 dB(A)

Audio outputsbalanced XLR, switchable to -30 or 0 dBm ; unbalanced TS 1/4" jack

Audio output level+9 dBu (max.)

Antenna inputs2x 50-ohm BNC female connectors

Transmitter battery indicationlow battery

Power supply12 V / 500 mA DC

Dimensions200 x 44 x 190 mm (7.8 x 1.7 x 7.4 in.)

Weight972 g (2.2 lbs.)Item# 3300H00220

General Specifications

Switching bandwidth30.5 MHz (depending on local regulations)

ModulationFM

Sensitivity6 dB $\mu$ V / -100 dBm

Receiver typeSuper heterodyne

Diversity system $\mu$ C controlled space diversity

Audio bandwidth35 to 20,000 Hz

THD at 1 kHz<0.3%

Signal-to-noise120 dB(A)

Audio outputs balanced XLR, switchable to -30 or 0 dBm ; unbalanced TS 1/4" jack

Audio output level +9 dBu (max.)

Antenna inputs 2x 50-ohm BNC female connectors

Transmitter battery indication low battery

Power supply 12 V / 500 mA DC

Dimensions 200 x 44 x 190 mm (7.8 x 1.7 x 7.4 in.)

Weight 972 g (2.2 lbs.) Item# 3300H00220

#### General Specifications

Switching bandwidth 30.5 MHz (depending on local regulations)

Modulation FM

Sensitivity 6 dB $\mu$ V / -100 dBm

Receiver type Super heterodyne

Diversity system  $\mu$ C controlled space diversity

Audio bandwidth 35 to 20,000 Hz

THD at 1 kHz < 0.3%

Signal-to-noise 120 dB(A)

Audio outputs balanced XLR, switchable to -30 or 0 dBm ; unbalanced TS 1/4" jack

Audio output level +9 dBu (max.)

Antenna inputs 2x 50-ohm BNC female connectors

Transmitter battery indication low battery

Power supply 12 V / 500 mA DC

Dimensions 200 x 44 x 190 mm (7.8 x 1.7 x 7.4 in.)

Weight 972 g (2.2 lbs.)