

Item# 3302H00190

General Specifications

Audio frequency bandwidth 35 - 20000 Hz

Signal to Noise 120 dB-A

THD at 1 kHz 0.7 Prozent

Peak deviation 48 kHz

Nominal deviation 20 kHz

Radio Output Power (min/max) 10 to 50 mW

Transmitter Synchronization Infrared

Mute Switch Type Jack Mono (1/4")

Mute Switch Gender Female

Switching bandwidth 30 MHz

Recommended simultaneous channels 25

Number of selectable frequencies 1220 (selectable in 25kHz steps)

Frequency Selection Selectable frequency in 25kHz steps

Radio range (Line of sight) 100m (depending on antenna system)

Switchable RF power no

Pilot Tone yes

Dimensions

Length 30 mm

Height 73.5 mm

Width 60 mm

Design

Body plastic

Finish black

Audio Input

TypeMini XLR

GenderFemale

Contacts3-pin

Maximum audio level12 dB

Battery

Battery typeFR 6 AA lithium battery

Number of batteries2

Operating time14 h

Battery 2

Battery typeHR 6 AA (NiHM) rechargeable battery

Compatibel Charging SystemCU401

Number of batteries2

Operating time8 h

Battery 1

Battery typeLR6 AA alkaline Battery

Number of batteries1

Operating time7 h