

Item# 3302H00220

General Specifications

Audio frequency bandwidth35 - 20000 Hz

Signal to Noise120 dB-A

THD at 1 kHz0.7 Prozent

Peak deviation48 kHz

Nominal deviation20 kHz

Radio Output Power (min/max)10 to 50 mW

Transmitter SynchronizationInfrared

Mute Switch TypeJack Mono (1/4")

Mute Switch GenderFemale

Switching bandwidth30 MHz

Recommended simultaneous channels35

Number of selectable frequencies1220 (selectable in 25kHz steps)

Frequency SelectionSelectable frequency in 25kHz steps

Radio range (Line of sight)100m (depending on antenna system)

Switchable RF powerno

Pilot Toneyes

Dimensions

Length30 mm

Height73.5 mm

Width60 mm

Design

Bodyplastic

Finishblack

Audio Input

TypeMini XLR

GenderFemale

Contacts3-pin

Maximum audio level12 dB

Battery

Battery typeFR 6 AA lithium battery

Number of batteries12

Operating time14 h

Battery 2

Battery typeHR 6 AA (NiHM) rechargeable battery

Compatibel Charging SystemCU411

Number of batteries12

Operating time8 h

Battery 1

Battery typeLR6 AA alkaline Battery

Number of batteries1

Operating time7 h