

PRODUCT SPECIFICATION

Frequency bands: A: 530,025 – 559,000 MHz; U1: 606,100 – 613,900 MHz; U2: 614,100 – 629,900

MHz; B1: 748,100 – 751,900 MHz; B2: 774,100 – 777,900 MHz; M: 826,300 –

831,000 MHz; D: 863,100 – 864,900 MHz; K: 925,100 – 931,850 MHz

Diversity system: Antenna switching

RF output: 10, 20 or 50 mW (depending on frequency band)

Audio bandwidth: 40 – 20 000 Hz (+/- 3dB)

Tuning range: Up to 30 MHz (depending on frequency band)

Max. channels: Up to eight compatible channels within one frequency band

Frequency selection: Fixed frequencies

Modulation: FM

Radio range (Line of sight): 30 meter (with external antennas further distances achievable)

Rack size ½ Racksize (19")

Dimensions: 150 x 44 x 200 mm

Item number: 3410H00...

PRODUCT SPECIFICATION

Type: Three pin mini XLR connector (female)

Maximum audio level: 12dB

Rated Impedance: 1 Ohms

Audio bandwidth: 40 – 20 000 Hz (+/- 3dB)

Signal to noise: 105 dB-A

THD at 1kHz: 0.8%

Transmitter synchronization: Manual

Battery type: AA battery (LR 6 AA alkaline battery or HR 6 AA (NiHM) rechargeable battery)

Operating time: Up to eight hours with one AA battery

Dimensions: 60 x 75,5 x 30 mm

Weight: 214g

Item number: 3412H00...