

AKG PZM10 Specs

Microphone

Form Factor	Boundary/Surface-Mount
Capsule	Electret Condenser
Polar Pattern	Hemispherical/Half-Omnidirectional
Pad	<i>None</i>
High-Pass Filter	<i>None</i>

Performance

Frequency Range	80 Hz to 20 kHz
Maximum SPL	120 dB SPL (3% THD)
Impedance	240 Ohms (Balanced)
Load Impedance	1000 Ohms (Minimum, Recommended)
Sensitivity	2.5 mV/Pa (Open Circuit Voltage) -52 dBV/Pa (Open Circuit Voltage)

Signal-to-Noise Ratio 68 dB (at 1 Pa/94 dB SPL)

Equivalent Noise Level 26 dB SPL A-Weighted (Typical)

Connectivity

Output Connectors **1 x** XLR 3-Pin Male

Power

Operating Voltage 12 to 48 V (Phantom Power)

Operating Current Consumption 400 μ A

Physical

Color White

Construction Material Steel

Dimensions \varnothing : 1.3 x L: 2.8" / \varnothing : 3.2 x L: 7.2 cm

Weight 2.6 oz / 73.6 g

Packaging Info

Package Weight 0.55 lb

Box Dimensions (LxWxH) 5.9 x 3.85 x 2.65"
