

AKG PZM10LL Specs

Microphone

Form Factor	Boundary/Surface-Mount
Capsule	Electret Condenser
Polar Pattern	Hemispherical/Half-Omnidirectional
Pad	<i>None</i>
High-Pass Filter	<i>None</i>

Performance

Frequency Range	80 Hz to 20 kHz
Maximum SPL	120 dB SPL (3% THD)
Impedance	240 Ohms (Balanced)
Load Impedance	1000 Ohms (Minimum, Recommended)
Sensitivity	2.5 mV/Pa (Open Circuit Voltage) -52 dBV/Pa (Open Circuit Voltage)

Signal-to-Noise Ratio	68 dB (at 1 Pa/94 dB SPL)
-----------------------	---------------------------

Equivalent Noise Level	26 dB SPL A-Weighted (Typical)
------------------------	--------------------------------

Connectivity

Output Connectors	1 x Pigtail
-------------------	--------------------

Power

Operating Voltage	12 to 24 V (Phantom Power)
-------------------	----------------------------

Operating Current Consumption	400 μ A
-------------------------------	-------------

Physical

Color	White
-------	-------

Construction Material	Steel
-----------------------	-------

Dimensions	\varnothing : 1.3 x L: 2.8" / \varnothing : 3.2 x L: 7.2 cm
------------	---

Weight	2.6 oz / 73.6 g
--------	-----------------

Packaging Info

Package Weight 0.5 lb

Box Dimensions (LxWxH) 5.8 x 3.8 x 2.6"
