

## Item# 3302H00240

- General Specifications
- Audio frequency bandwidth 35 - 20000 Hz
- Signal to Noise 120 dB-A
- THD at 1 kHz 0.7 Prozent
- Peak deviation 48 kHz
- Nominal deviation 20 kHz
- Radio Output Power (min/max) 10 to 50 mW
- Transmitter Synchronization Infrared
- Mute Switch Type Jack Mono (1/4")
- Mute Switch Gender Female
- Switching bandwidth 30 MHz
- Recommended simultaneous channels 25
- Number of selectable frequencies 1220 (selectable in 25kHz steps)
- Frequency Selection Selectable frequency in 25kHz steps
- Radio range (Line of sight) 100m (depending on antenna system)
- Switchable RF power no
- Pilot Tones
- Dimensions
- Length 30 mm
- Height 73.5 mm
- Width 60 mm
- Design
- Body plastic
- Finish black

- Audio Input
- TypeMini XLR
- GenderFemale
- Contacts3-pin
- Maximum audio level12 dB
- Battery
- Battery typeFR 6 AA lithium battery
- Number of batteries2
- Operating time14 h
- Battery 2
- Battery typeHR 6 AA (NiHM) rechargeable battery
- Compatibel Charging SystemCU401
- Number of batteries2
- Operating time8 h
- Battery 1
- Battery typeLR6 AA alkaline Battery
- Number of batteries1
- Operating time7 h