

# AKG Presenter Set Specs

## Receiver

---

Frequency Range                      Band 8 / 570.1 to 600.5 MHz

---

Switching Bandwidth                -/ < 30.5MHz (country dependent)

---

Sensitivity                              6.3 dBV / -100dBm

---

Diversity Circuitry                    Microprocessor-controlled diversity

---

Modulation                             Wideband FM

---

Audio Bandwidth                      35 - 20,000Hz ( $\pm 3$ dB)

---

THD                                        -/ < 0.3%

---

Signal-to-Noise Ratio                typ. 120 dB(A)

---

Audio Outputs                         1 x XLR sockets balanced  
1 x TS 1/4" (6.3mm) jack sockets  
unbalanced

---

Dimensions                              1/2 19inch 1U rack  
7.8 x 1.7 x 7.4" (202 x 44 x 190mm)

---

Weight                                    2.2 lb (972g)

---

## Transmitter

---

Switching Bandwidth	-/< 30.5 MHz (country dependent)
RF Output Power	10 or 50mW (ERP, country dependent)
Modulation	Wideband FM
Audio Input	TB3M / 3-pin mini-XLR socket (max. 2.5Vrms)
Audio Bandwidth	35 - 20 000Hz ( $\pm$ 3dB)
THD	-/< 0.7%
Signal-to-Noise Ratio	> 120 dB(A)
Battery Life	-/< 7 hours with one 1.5 V LR6 AA alkaline battery -/< 8 hours with one 1.2 V HR6 AA rechargeable battery (min. 2100 mAh) -/< 14 hours with one 1.5 V FR6 AA lithium battery
Dimensions	2.4 x 2.9 x 1.2" (60 x 73.5 x 30mm)
Weight	3.2 oz (90g)