

**Item# 3201H00050**

- General Specifications
- Audio frequency bandwidth 35 - 20000 Hz
- Signal to Noise 120 dB-A
- THD at 1 kHz 0.3 Prozent
- Operating temperature range -10 to 55 Celsius
- Peak deviation 48 kHz
- Switching bandwidth 30 MHz
- Recommended simultaneous channels 50
- Number of selectable frequencies 1220 (selectable in 25kHz steps)
- Frequency Selection Selectable frequency in 25kHz steps
- Radio range (Line of sight) 100m (depending on antenna system)
- Switchable RF power no
- Modulation FM (Frequency Modulation)
- Encryption No encryption
- Diversity True Diversity
- Pilot Tones yes
- Nominal deviation 20 kHz
- Radio Output Power (min/max) 10 to 50 mW
- Microphone head versions C535 WL1
- Transmitter Synchronization Manual
- Dimensions
- Height 247 mm
- Width 51 mm
- Net Weight 125 g

- Design
- Body metal
- Finish black
- Battery
- Battery\_English type AKG BP 4000
- Compatible Charging System CU4000
- Number of batteries 1
- Operating time 12 h
- Battery 2
- Battery type HR 6 AA (NiHM) rechargeable battery
- Compatible Charging System CU4000
- Number of batteries 2
- Operating time 12 h
- Battery 1
- Battery type LR6 AA alkaline Battery
- Number of batteries 2
- Operating time 15 h