

# AKG C414 XL II Specs

## Microphone

---

Polar Pattern	Cardioid, Figure-8, Hypercardioid, Omnidirectional, Wide-Angle Cardioid
---------------	---

---

Pattern Selection	Switched
-------------------	----------

---

Pad	-6 dB -12 dB -18 dB
-----	---------------------------

---

High-Pass Filter	40 Hz 80 Hz 160 Hz
------------------	--------------------------

---

## Performance

---

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

---

Maximum SPL	140 dB SPL
-------------	------------

---

Impedance	200 Ohms
-----------	----------

---

Load Impedance	2200 Ohms
----------------	-----------

---

Sensitivity	23 mV/Pa
-------------	----------

---

Dynamic Range	134 dB A-Weighted
---------------	-------------------

---

Signal-to-Noise Ratio	88 dB A-Weighted
-----------------------	------------------

---

Equivalent Noise Level	6 dB A-Weighted
------------------------	-----------------

---

## Connectivity

---

Output Connectors	<b>1 x</b> XLR 3-Pin
-------------------	----------------------

---

## Power

---

Operating Voltage	48 V
-------------------	------

---

Operating Current Consumption	4.5 mA
-------------------------------	--------

---

## Physical

---

Operating Temperature	14 to 140°F / -10 to 60°C
-----------------------	---------------------------

---

Dimensions	L: 6.3" / L: 16 cm
------------	--------------------

---

Weight	10.58 oz / 300 g
--------	------------------

---

# Packaging Info

---

Package Weight 5.695 lb

---

Box Dimensions (LxWxH) 15.65 x 12.25 x 3.95"

---